

EXPRESS MAIL NO. EV 005 610 281 US

DATE OF MAILING 2/6/88

Our Case No. 9281-4274
Client Reference No. S US00206

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:)
Hideki Kondo)
Serial No. To be Assigned)
Filing Date: Herewith)
For Waveguide for Microwave Device)

PRELIMINARY AMENDMENT

Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

Prior to examination of the above-identified application, please amend the application as follows:

In the Claims

Please rewrite Claim 1 as follows:

1. (Amended) A waveguide for a microwave device, comprising:
a frame housing a high-frequency circuit therein; and
a lid attached to a sidewall of the frame,
wherein at least one of the frame and the lid has a waveguide groove
formed therein and extending along a mating surface between the frame and the lid.


Please rewrite Claim 4 as follows:

4. (Amended) The waveguide according to Claim 2, wherein the sub-casing is arranged inside four sidewalls of the main casing and the main casing has a through-hole, through which the probe passes, formed in the sidewall to which the lid is attached.

REMARKS

Applicant has rewritten Claims 1 and 4. The changes from the previous version to the rewritten version are shown in attached Appendix A, with strikethrough for deleted matter and underlining for added matter.

Respectfully submitted,



Gustavo Siller, Jr.
Registration No. 32,305
Attorney for Applicant

BRINKS HOFER GILSON & LIONE
P.O. BOX 10395
CHICAGO, ILLINOIS 60610
(312) 321-4200

APPENDIX A
Waveguide for Microwave Device
Attorney Docket No. 9281-4274
Inventor Hideki Kondo

In the Claims

Please amend Claim 1 as follows:

1. (Amended) A waveguide for a microwave device, comprising:
a frame housing a high-frequency circuit therein; and
a lid attached to a sidewall of the frame,
wherein at least one of the frame and the lid has a waveguide groove
formed therein and extending along the mating surface between the frame and the
lid.

Please amend Claim 4 as follows:

4. (Amended) The waveguide according to Claim 2, wherein the sub-
casing is arranged inside the four sidewalls of the main casing and the main casing
has a through-hole, through which the probe passes, formed in the sidewall to which
the lid is attached.